

POWR-FLITE®

O-Z Care System

The Professional Choice for Odor Neutralizing



- Eliminates smoke, pet odor, mold, mildew and more.
- Quickly deodorizes hotel/motel, hospital and meeting rooms.
- Excellent for freshening up cars, buses, boats and aircraft.
- 2.65 grams/hr., 7.95 p.p.m.
- Effective for areas up to 40,000 cubic feet.
- 30-hour programmable timer with adjustable ozone output levels.
- Power supply overload protection.
- Tested and proven to maintain proper activated oxygen levels.
- High-density ceramic & stainless steel electrodes.
- No plates or UV tubes to maintain.
- Two-year limited warranty on parts.
- Lifetime warranty on ozone electrodes (patented) and body.

O-Z Care Systems destroy odor-causing bacteria and molecules. This economical environmental odor neutralizer actually destroys the source of the odor and leaves pure fresh oxygen in its place. The O-Z unit is a large-capacity ozone generator ideal for commercial use. It is excellent for smoke damage, mold, mildew, pet odor and other sources of odor commonly found in building maintenance and refurbishing. The O-Z unit will eliminate odor in any indoor location, including basements, kitchens, bathrooms and more. It also provides rapid deodorizing for hotel/motel rooms, meeting rooms, used cars and boats.

800.880.2913

www.PowrFlite.com

Expand Your Line with the Power of O-Zone Odor Neutralizing

Ozone occurs naturally in the environment. The most common exposure to ozone occurs when there is a thunder storm. The fresh smell you notice is from the ozone released during the storm.



100 CFM fan rapidly replaces air with ozone

The O-Z Care System creates ozone by exposing oxygen in the atmosphere to high-density ceramic and stainless steel electrodes. When the oxygen in the air comes in contact with the electrodes it brings the oxygen molecules (O₂) together to form ozone (O₃). The O-Z unit injects the ozone into the air. When the ozone is introduced, it disperses and mixes with the air.

Once ozone molecules come in contact with any organic material including soil, micro-organisms,

indoor allergens, odors for cleaning residue, it will release an oxygen atom which attaches to the organic material.

This reaction oxidizes the organic material and releases oxygen into the air. This causes the residue to break down and release the bond from the surface being cleaned.



High density ceramic and stainless steel electrodes

Ozone is a stronger oxidant than other chemicals like chlorine and reacts much more quickly with organic materials. Ozone has proven to be effective wherever removal of organic contaminants is important.

Ozone is safe in professional applications and studies show the O-Z Care System is proven to maintain proper activated oxygen levels.

	Specifications
Air Movement	2.65 grams/hr., 7.95 p.p.m.
Timer	30-hour programmable
Switches	Touch pad
Fan Motor	100 CFM
Tank Construction	Ultra heavy-duty poly housing
Exhaust Hose	10 foot vac hose (optional)
Power Cord	5 ft. grounded
Max Effectiveness	40,000 cubic feet
Electrodes	High-density ceramic and stainless steel
Weight	12.5 lbs.
Warranty	2 years parts, Lifetime on electrodes and housing

Power-Flite
COMMERCIAL FLOOR CARE EQUIPMENT

